

Item no.

Connector type
 For cable

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ω
Amp. Rating (measured)	Cable data
(calculated)	Cable data
Transfer Impedance (CoMeT)	<5,0 mΩ/m @ 5-30MHz
	<0,11 mΩ/con. @ 5-30MHz
Shielding Effectiveness (CoMeT)	>110 dB @ 30- 862MHz
	>100 dB @ 862-3000MHz



All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.

Return Loss (IEC 61169-1)
(RF Analyzer HP 8714C)

	Better than	Typical
0.3 - 500 MHz	-33 dB	-36,1 dB
500 - 860 MHz	-30 dB	-35,8 dB
860 - 1000 MHz	-29 dB	-35,3 dB
1000 - 1750 MHz	-25 dB	-31,7 dB
1750 - 2150 MHz	-24 dB	-29,9 dB
2150 - 3000 MHz	-23 dB	-28,9 dB

Insertion Loss Max.

	Better than	Typical
0.3 - 500 MHz	-0,06 dB	-0,01 dB
500 - 860 MHz	-0,06 dB	-0,01 dB
860 - 1000 MHz	-0,06 dB	-0,01 dB
1000 - 1750 MHz	-0,07 dB	-0,02 dB
1750 - 2150 MHz	-0,07 dB	-0,02 dB
2150 - 3000 MHz	-0,07 dB	-0,02 dB

Temperature

Installing	-5° to +50° C
Operating	-40° to +100° C
Storing	-40° to +100° C

Intermodulation

	IM3	IP3-value
3rd Order (@2x100mW)	< -120 dBc	> +80 dBm

Inner Conductor Resistance

(@ 1 A DC)	Cable data
------------	------------

Sealing Test

(IEC IP-code)	-
---------------	---

Insulation Resistance

(@ 500 VDC)	Cable data
-------------	------------

O-rings

-

Dielectric Strength

DC Test Voltage	Cable data
-----------------	------------

Base Material

Body Parts	Brass CuZn39Pb3 / CuZn36Pb3 / POM
Inner Conductor	-

Max. Tensile Strength

Overall	125 N
	12,7 Kgf

Plating

Body Parts	Nitin-6
Inner Conductor	-

Torsional Strength

(Connector / Cable)	* NATM
---------------------	--------

Insulators

-

Test performed by

Troels V. Kristensen

Date of release

April 23, 2009

Remarks

* Not Able To Measure(NATM): The cable starts to twist without the connector loosing its grip.

ISO 9001:2000 / ISO 14001 certified

Distributor:

CABELCON
connectors

Corning Cabelcon ApS, Industriparken 10, DK 4760 Vordingborg
 Tel: +45 55 98 55 99 · Fax: + 45 55 98 55 04
 E-mail: cabelcon@cabelcon.dk · www.cabelcon.dk