

Item no. 53054003-01

FM-TL540TI  
CommScope QR 540 JCA

Frequency Range 0.3 - 3000 MHz  
Impedance (Nom.) 75 Ω  
(calculated) 4.5 A @10°C increase  
6.3 A @20°C increase

Product photo



Transfer Impedance (CoMeT) Class A++  
<0.9 mΩ/m @ 5-30MHz

Screening Attenuation(CoMeT) Class A++  
>130 dB @ 30-1000MHz  
>130 dB @ 1000-2000MHz  
>120 dB @ 2000-3000MHz

Return Loss (IEC 61169-1)	Better than	Typical
0.3 - 500 MHz	-35 dB	38.0 dB
500 - 860 MHz	-33 dB	-36.4 dB
860 - 1000 MHz	-33 dB	-36.2 dB
1000 - 1750 MHz	-33 dB	-35.7 dB
1750 - 2150 MHz	-32 dB	-34.7 dB
2150 - 3000 MHz	-30 dB	-32.7 dB

Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-0.06 dB	-0.01 dB
500 - 860 MHz	-0.06 dB	-0.01 dB
860 - 1000 MHz	-0.06 dB	-0.01 dB
1000 - 1750 MHz	-0.06 dB	-0.01 dB
1750 - 2150 MHz	-0.06 dB	-0.01 dB
2150 - 3000 MHz	-0.06 dB	-0.01 dB

Temperature  
Installing -5° to +50° C  
Operating -40° to +70° C  
Storing -40° to +70° C

Intermodulation IM3  
3rd Order (@2x+30dBm) -155 dBc

Inner Conductor Resistance (@ 1 A DC) <1.5 mΩ

Sealing Test (IEC IP-code) IP X8 30 meter / 8 hours

Insulation Resistance (@ 500 VDC) >200 GΩ

O-rings EPDM

Dielectric Strength DC Test Voltage >2.0 KV

Base Material  
Body Parts Brass CuZn39Pb3  
Inner Conductor Brass CuZn39Pb3

Max. Tensile Strength  
Overall >1800 N  
Inner Conductor >500 N

Plating  
Body Parts Nitin-6  
Inner Conductor Nitin-6

Torsional Strength (Connector / Cable) >6.5 Nm

Insulators COC (Topas) / PP with Glass

Test performed by Sven-Erik Sandberg  
Date of release January 08, 2015

Remarks

*All tests performed using instruments calibrated in accordance to our ISO 9001 certification.  
Further technical specifications and installation instructions can be obtained on request.*